

PACIFIC SWIMMING POOL SALT			
COMPONENTS	SPECIFICATION	TYPICAL	DSL Test Method <i>(Reference Method)</i>
Sodium Chloride as NaCl - Minimum moisture free	Min 99.5%	99.7%	DSL Pt.5 (BP)
Moisture Content	Max 0.2%	0.05%	DSL Pt. 12 (BS 7319:Part 2:1990)
Matter Insoluble in water	Max 0.05%	0.015%	DSL Pt. 11 (BS 7319:Part 3:1990)
Sulphate as Na ₂ SO ₄	Max 0.30%	0.07% (700 mg/kg)	DSL Pt. 14 (BS 7319:Part 4:1990)
Calcium as Ca	Max 0.06%	0.025% (250 mg/kg)	DSL Pt. 6 (BS 7319:Part 5:1990)
Magnesium as Mg	Max 0.04%	0.003% (30 mg/kg)	DSL Pt. 6 (BS 7319:Part 5:1990)
Arsenic as As	NS	<0.1 mg/kg	DSL Pt. 2 (BS 4404:1968)
Copper as Cu	Max 2 mg/kg	<0.5 mg/kg	DSL Pt. 4 (BS 7319:Part 7:1990)
Lead as Pb	NS	<0.1 mg/kg	DSL Pt. 4 (BS 7319:Part 8:1990)
Iron as Fe	Max 10 mg/kg	2.0 mg/kg	DSL Pt. 4 (BS 7319:Part 11:1990)
Potassium as K	NS	230 mg/kg	DSL Pt. 19 (BP)
Additives: Anticaking Agent as Na ₄ [Fe(CN) ₆]	Max 50 mg/kg	8 mg/kg ¹	DSL Pt. 9 (BS 7319:Part 12:1990)

Notes: < Less than > Greater than ppm = mg/kg = (% x 10,000)
 1. Mount Maunganui Refinery only

GRADE DESCRIPTION:

Specially prepared for chlorine generation in domestic pools fitted with salt chlorinators. Salt is ex stack, crushed, washed and kiln dried.

Recommended directions for use are printed on the pack

COUNTRY OF ORIGIN: Product of New Zealand

GRAIN SIZE: Crushed, Maximum 5 mm.

BULK DENSITY: Nominally: loose 1.11g/ml, compacted 1.32g/ml

COMPLIANCE *Dominion Salt is ISO 9001 certified*

PACK: 20kg pack

PALLETS: Standard pallet configuration is 60 x 25kg bags (1.2 tonnes per pallet). The salt is stretch wrapped and capped on pallets

Issue Date: 22.11.16
 Issue No: 5